



NOTES:

1. TUNNEL TOP OF RAIL SIGN TO BE AFFIXED ON SIDE OF PORTAL ON MASONRY, FASTENED WITH 5/16" EXPANSION BOLTS, OR MAY BE ATTACHED USING LIQUID NAILS OR SIMILAR MATERIAL.
2. TUNNEL TOP OF RAIL SIGN TO BE PLACED 6" BELOW THE BOTTOM OF STRUCTURE MARKER SIGN, DRAWING 0505.
3. IF CONDITIONS DO NOT ALLOW FOR MOUNTING ON PORTAL, TUNNEL SIGN WILL BE PLACED ON POST ON ENGINEER'S SIDE OF TRACK (IF POSSIBLE) IMMEDIATELY ADJACENT TO TUNNEL PORTAL. PLACE SIGN A MINIMUM OF 10'-0" FROM GAUGE SIDE OF NEAREST RAIL.
4. SURVEY MARKS TO BE PLACED THROUGHOUT TUNNEL.
5. SIGN TO BE 3290 SILVER 3M ENGINEER GRADE BACKGROUND ON 0.080" 3105 SHEET ALUMINUM.

FOR LETTERING, SEE STD DWG 0501
FOR MOUNTING DETAILS, SEE STD DWG 0599

STD DWG
0541

ITEM NO.
393-6318

UNION PACIFIC
ADOPTED: SEP. 21, 2020
REVISED:
FILE NO.: 0541

STD DWG
0541