



SEE TABLE FOR VOLTAGE OPTIONS

VOLTAGE	ITEM NUMBER
550	393-1001
2300	393-1002
2400	393-1000
4160	393-1003
7200	393-1004
7620	393-1005
7960	393-1006
12.4K	393-1007
13.2K	393-1008
13.8K	393-1009

- NOTES:
- HIGH VOLTAGE SIGN TO BE DIGITALLY OR SCREEN PRINTED, MUTCD YELLOW CMYK CODE 0/5/100/0, SUBSTRATE TO BE 3MM PALIGHT PVC, SIGN TO HAVE AN OVERLAMINATE APPLIED FOR UV PROTECTION.
 - ITEM NO. 393-8018 AND ITEM NO. 393-8022 TO BE NO. 3290 SILVER 3M ENGINEER GRADE BACKGROUND ON 0.080" 3105 ALUMINUM, EXCEPT BOXED AREA AROUND THE WORD "DANGER" WHICH WILL BE REVERSED SCREENED 3M NO. 882 TRANSPARENT RED WITH LETTERS TO BE SILVER.
 - SIGNS TO BE POSTED IN THE MOST CONSPICUOUS PLACE AT ALL POINTS WHERE GASOLINE IS STORED.

FOR LETTERING, SEE STD DWG 0501
FOR MOUNTING DETAILS, SEE STD DWG 0599

REF PREVIOUS U.P. STD PAGE 0527-A

**UNION PACIFIC RAILROAD
ENGINEERING STANDARDS**

HAZARD SIGNS

UNION PACIFIC
ADOPTED: SEP. 21, 2020
REVISED: JAN. 22, 2021
FILE NO.: 0517

STD DWG
0517B

STD DWG
0517B